

FCL Components Touch Panels

Feather Touch - Long Life 4-Wire series

FCL Components Resistive Touch Panel Specification

Features

- Superior quality 4-wire resistive touch panels
- Available in light input force types (min. 0.02N) or standard force type
- Light input force with dual input gesture supports PCAP comparable user experience
 - Pinch, Zoom, Rotate, Swipe or Flick action detection by the application or operating system
- Excellent specification and high quality panels for a wide range of applications
- Pen/finger input support
- 80% transparency typical
- New optional clear film with enhanced transparency and reduced friction
- Custom antibacterial and antiviral functionality
- RoHS compliant



■ Feather Touch - Long Life 4-Wire Resistive Touch Panel Part Numbers

Size	Aspect Ratio	Part number	Transparent area (mm)	Glass thickness (mm)	Tail (Flex) length mm	Transparency %
22	wide	FID-1144-001-A22	479.8 x 303.1	1.8	120	80
19	4x3	FID-1143-001-A19	382.9 x 307.7	1.8	120	80
15	4x3	FID-1142-001-A15	311.0 x 234.2	1.8	120	80
15	4x3	FID-1141-001-A15	309.0 x 233.0	1.8	120	80
12.1	4x3	FID-1135-001-A12	251.0 x 189.5	1.1	75	80
10.4	4x3	FID-1134-001-A10	216.0 x 163.0	1.1	75	80
10.4	4x3	FID-1133-001-A10	216.6 x 164.6	1.1	75	80
10.1	wide	FID-1132-001-A10	229.0 x 131.5	1.1	75	80
10.1	wide	FID-1131-001-A10	223.4 x 141.5	1.1	75	80
8.4	4x3	FID-1125-001-A08	175.9 x 133.3	1.1	61	80
8.4	4x3	FID-1124-001-A08	176.0 x 133.5	1.1	61	80
7	wide	FID-1123-001-A07	162.4 x 98.6	1.1	61	80
7	wide	FID-1122-001-A07	159.4 x 97.4	1.1	61	80
5.7	4.3	FID-1121-001-A05	119.2 x 89.4	1.1	61	80

- Notes: Full specifications are available - please contact your local Sales Representative or use the Contact Form to request


■ Controller Boards

Part Number	Type	Support Interface	Features	Dimensions (mm)
FID-1850-170	4-wire	RS232C	Single input	75.0 x 30.0 x 8.5
FID-1850-150	4-wire	USB (full speed)	Single input	75.0 x 30.0 x 8.5
FID-1850-160	4-wire	USB (full speed)	Dual / single input	60.0 x 30.0 x 5.2

■ Control IC


Part Number	RTP Type	Support Interface	Feature	Dimensions (mm)
FID-1860-013	4-wire	Asynchronous serial	Dual/single input	7.0 x 7.0 x 1.7 (body) 48 pin LFQFP
FID-1860-014	4-wire	USB (full speed)	Dual/single input	7.0 x 7.0 x 1.7 (body) 48 pin LFQFP

■ Dimension example



■ System description and block diagram

FCL Components' touch panel in combination with a control IC chip or control board is used for transfer the co-ordinate data to the host system.



■ General notes

Touch panels are made of glass, so care must be taken in handling them. Do not stress, pile, bend, lift by the cable or put any stress on the film, for example moving by film face vacuum. In order to clean wring dry a cloth which has been emersed in a natural detergent.

DO NOT use any organic solvent, acid or alkali solution. Watch the edge of the panel when cleaning, again for safety reasons.

■ Detailed specifications

Complete specification document is available upon request.

■ Electrical: Touch Panels

Rated voltage	DC 5V
Switch bounce (chattering)	20ms maximum
Insulation resistance	10MΩ minimum

■ Environmental: Touch Panels

Operating temperature	-5°C to 60°C
Storage temperature	-30°C to 70°C
Operating humidity *1	20% to 90%
Storage humidity *1	10% to 90% RH

*v: Maximum wet bulb temperature of 38°C

Contact

Japan
 FCL COMPONENTS LIMITED
 Shinagawa Seaside Park Tower
 12-4, Higashi-shinagawa 4-chome,
 Tokyo 140 0002, Japan
 Tel: +81 3 3450 1682
 Email: fcl-contact@cs.fcl-components.com

Europe
 FCL COMPONENTS EUROPE B.V.
 Diamantlaan 25
 2132 WV Hoofddorp
 Netherlands
 Tel: +31 23 5560910
 Email: info@fcl-components.eu

China
 FCL CCOMPONENTS (SHANGHAI) CO., LTD.
 Unit 1105, Central Park –Jing An, No.329 Heng Feng
 Road, Shanghai 200070, China
 Tel: +86 021 3253 0998
 Email: fcsh@fcl-components.com

North and South America
 FCL COMPONENTS AMERICA, INC.
 2055 Gateway Place, Suite 480
 San Jose, CA 95110 U.S.A.
 Tel: +1 408 745 4900
 Email: fcai.components@fcl-components.com

Asia Pacific
 FCL COMPONENTS ASIA, LTD.
 No. 20 Harbour Drive, #07-01B
 Singapore 117612
 Tel: +65 6375 8560
 Email: fcal@fcl-components.com

Hong Kong
 FCL CCOMPONENTS HONG KONG Co., LIMITED
 Room 13, 23/F, Seapower Tower, Concordia Plaza,
 No.1 Science Museum Road,
 Tsim Sha Tsui East, Kowloon, Hong Kong
 Tel: +852 2881 8495
 Email: fcsh@fcl-components.com

Web: www.fcl-components.com/en/

Copyright

All trademarks or registered trademarks are the property of their respective owners. FCL Components America or its affiliates do not warrant that the content of datasheet is error free. In a continuing effort to improve our products FCL Components America, Inc. or its affiliates reserve the right to change specifications/datasheets without prior notice.

Copyright ©2024 FCL Components America, Inc. All rights reserved. Revised April 25, 2024.